




MARTE PNEUMATICA

MARS PNEUMATIC

PRESSA DA STIRO A
FUNZIONAMENTO
PNEUMATICO

PNEUMATIC IRONING
PRESS



UNIVERSALE LAVANDERIA
UNIVERSAL LAUNDRY



PACKAGING



ACCESSORI APPLICABILI A RICHIESTA

ACCESSORIES AVAILABLE BY REQUEST

Aspiratore 0,5 HP
Vacuum motor 0,5 HP

Braccio inox
Stainless steel arm

Caldia interna 26 l. (10-12-15 KW) 400 V+N - 50 Hz /
230V - 50 Hz
Built-in 26 l. Boiler (10-12-15 KW) 400 V+N 50 Hz / 230V
- 50 Hz

Chiusura piano superiore a pedale + telaio salvamani
Head closing by pedal + safety frame

Compressore da 1,5 HP
1,5 HP compressor

Ferro da stiro con gruppo vapore
Iron with condensate separator

Kit pistola aria/vapore
Steam/air gun kit

Kit soffiaggio
Blowing kit

Lato superiore lucido
Polished top head

Caratteristiche tecniche

Technical features

Ingombro - Overall dimensions

Imballo - Packing

Peso - Weight

Consumo medio vapore - Average steam consumption

Pressione aria compressa - Compressed air pressure

Pressione di esercizio vapore - Operating steam pressure

Diametro attacco aspiratore - Vacuum outlet diameter

Voltaggio standard - Standard voltage

Voltaggio a richiesta - Upon request

MARTE PNEUMATICA

Marte pneumatic

120×140×160 H cm

2,8 m³

200-300 kg (in base al modello -
according to model)

15÷20 Kg/h

6 BAR (richiesta - required)

5 BAR (richiesta - required)

100mm

230 V - 50 Hz

400 V+N - 50 Hz (solo con caldaia -
only with steam boiler)

